

DC 3-/4-wire Inductive Sensors

Cylinder designs, M8x1




TRIPLEPROX



SUPERSHORTIES

SUPERSHORTIES



Inductive Sensors

Global DC 3-wire

DC 3-/4-wire

Cylinder Designs

Block Designs

DC 2-wire

AC/DC 2-wire

AC 2-wire

Special Properties

Analog Distance measurement

Accessories

M8x1		Ø11x12 mm		Ø11x17 mm	
Not flush		Flush		Not flush	
6 mm		4 mm		6 mm	
0...4.8 mm		0...3.2 mm		0...4.8 mm	
■■■		■■		■■	
BES02W3		BES047J		BES047R	
BES M08MG1-PSC60F-S04G		BES G11EA-PSC40B-EP00,3-GS04		BES G11EA-PSC60F-EP00,3-GS04	
BES02W0					
BES M08MG1-NSC60F-S04G					
10...30 V DC		10...30 V DC		10...30 V DC	
2 V		2.5 V		2.5 V	
75 V DC		75 V AC (□)		75 V AC (□)	
200 mA		100 mA		100 mA	
Yes/Yes/Yes		Yes/Yes/Yes		Yes/Yes/Yes	
-25...+70 °C		-40...+85 °C		-40...+85 °C	
500 Hz		2 kHz		2 kHz	
Yellow LED		Yellow LED		Yellow LED	
IP 67		IP 67		IP 67	
CE		CE, cULus		CE, cULus	
Large switching distance		Short design		Short design	
Brass-coated		Stainless steel		Stainless steel	
PBT		LCP		LCP	
M12 connector, 4-pin		M12 connector, 4-pin		M12 connector, 4-pin	

