



## Display/Operation

<b>Keypad</b>	Membrane keypad
<b>Setting</b>	Input signal selection Decimal point Tare Scaling

## Electrical data

<b>Input resistance</b>	Voltage $\geq 50$ kOhm, current 10 Ohm
<b>Rated input current</b>	65 mA

## Environmental conditions

<b>Ambient temperature</b>	0...60 °C
<b>IP rating IEC 60529 (connector)</b>	IP20
<b>Relative humidity</b>	$\leq 80\%$
<b>Storage temperature</b>	-20...70 °C

## General data

<b>Approval/Conformity</b>	CE WEEE
<b>Function</b>	Analog value display
<b>Short description</b>	Digital display

## Material

<b>Housing material</b>	Plastic
-------------------------	---------

## Mechanical data

<b>Dimension</b>	72 x 48 x 96 mm
<b>IP rating (front housing)</b>	IP54
<b>Panel cut-out</b>	45 x 92 mm

## Output/Interface

<b>Analog inputs</b>	Analog, voltage/Analog, current (0...10 V/0...20 mA/4...20 mA)
<b>Cycle time min.</b>	200 ms
<b>Interface</b>	Analog, voltage/analog, current

## Range/Distance

<b>Resolution</b>	$\leq 12$ bits
-------------------	----------------

## Wiring Diagrams

