

GAALSHIP® HF 1000 A EMC

Armoured, power and control cable, EMC, 0,6/1 kV



ELETTROTEK KABEL® GAALSHIP® HF 1000 A EMC



Applications:

EMC power and control cables for fixed electrical installations aboard ships, not subject to mechanical risk complying with IEC 60092-352

Construction:

Conductor:	Plain annealed copper or Tinned annealed copper conductor Cl. 2 flexible up to 10 mm ² Cl. 5 from 16 mm ² , acc. to EN IEC 60228
Insulation:	GAALTHERM® 595
Cores color:	Acc. to DIN VDE 0293-308, HD 308 S2 from 6 cores black cores with consecutive numbers acc. to EN 50334 green-yellow earth-wire from 3 cores
Inner sheath (if any):	Halogen free compound or synthetic tape
Armour:	Plain or tinned annealed copper wires braid + 100% coverage plain annealed copper/polyester tape acc. to IEC 60092-350
Outer sheath:	Halogen free thermoplastic compound type SHF1, acc. to IEC 60092-360, Thickness acc. to IEC 60092-353
Marking:	ELETTROTEK KABEL® GAALSHIP® HF 1000 A EMC, cross nominal section sqmm, 0,6/1 kV, part n°, IEC 60092-353, IEC 60332-3-22, production plant, batch n°, production date, CE RoHS, progressive meter marking.

Type Approvals/Certificates:

RINA / RINAMIL (Registro Italiano Navale)
BV (Bureau Veritas)
LR (Lloyd's Register)
DNV-GL (Det Norske Veritas - Germanischer Lloyd)
ABS (American Bureau of Shipping)
RMRS (Russian Maritime Register of Shipping)
Other approvals on request

Resistance:



Flame and fire retardant acc. to:
EN IEC 60332-1-2,
EN IEC 60332-3-22



Halogen free acc. to:
EN IEC 60754-1/2



Smoke emission properties acc. to:
EN IEC 61034-1/2

Technical data:

Nominal voltage:	U ₀ /U 0,6/1 kV
Test voltage:	3,5 kV
Temperature range:	-40°C up to +90°C
<i>Installation temp.:</i>	-5°C
Short circuit temperature:	+250°C
Min. bending radius:	4 x Outer diameter

Features:

Sheathing and insulating materials acc. to: IEC 60092-360
Design guidelines acc. to IEC 60092-350/353
Choice and installation of electric cables acc. to IEC 60092-352
Cold bend test at low temperatures
acc. to IEC 60092-350 art. 8.9 and Annex E (-40°C)
Cold bend impact at low temperatures
acc. to IEC 60092-350 art. 8.9 and Annex E (-35°C)
On request class 5 conductor for sections up to 10 mm²

GAALSHIP® MARINE CABLES

GAALSHIP® HF 1000 A EMC

Armoured, power and control cable, EMC, 0,6/1 kV



ELETTROTEK KABEL® GAALSHIP® HF 1000 A EMC

Part no.	No. of cores x cross section n x mm ²	Outer sheath color	Outer diameter ca.mm			Cable weight approx. kg/km	Max. resistance of conductors at 20°C (Ohm/km)	Current rating in open air at 45°C (A)	Short circuit rating I sec. (kA)
			Min.	Nom.	Max.				
12091G73037M63	3 x 25 + 3 G 6	Black	26,1	30,6	33	1296	0,8 / 3,1	89	3,75
12091G73037M65	3 x 50 + 3 G 10	Black	31,3	35,8	38,4	2374	0,4 / 1,8	137	7,20
12091G73037M66	3 x 70 + 3 G 16	Black	36,6	41,1	43,8	3263	0,3 / 1,2	169	10,10
12091G73037M67	3 x 95 + 3 G 16	Black	41,2	45,7	48,5	4113	0,2 / 1,2	205	13,70
12091G72041M60	4 G 6	Black	13	15,2	17,1	646	3,1	36	0,95
12091G72041M61	4 G 10	Black	16	18,5	20,4	874	1,8	50	1,55

Other dimensions and colors available on request.